

This invention is concerned with improved weight systems for exercise equipment.

### BACKGROUND OF THE INVENTION

Many units of exercise equipment have been disclosed or put into actual use in which a cable is drawn against a resistance source by an individual exercising with the equipment. Typically, these units of equipment include a handle attached to one end of a cable with a resistance source, such as weights, attached to the other end of the cable and opposing the pulling of the cable. Different exercises can be performed by adjusting the vertical position at which the cable leaves the equipment. That adjustability, however, provides only a limited variety of exercises.

U.S. Patent No. 4,603,855 discloses exercise equipment in which the handle, grasped by the individual using the equipment, can undergo three degrees of movement as it is positioned for a selected exercise. Although such equipment provides added adjustability, whereby many more exercises are possible, the particular arrangement disclosed in this patent, which includes mounting the handle on a telescoping arm, lacks sufficient strength and stability when constructed from conventional components or becomes very expensive to manufacture when special components are used to provide greater strength and stability.

In other exercise equipment sold by Elgin Exercise Equipment Corporation of Des Plaines, Illinois, the handle grasped by the user is movable to the desired position by a trolley, which moves along a curved rod track. This equipment also provides added

facility for a variety of different exercises. However, the framework support structure of this exercise equipment, particularly the single arced bar used to relocate the egress point, also provides only limited strength and stability when constructed from conventional components or becomes very expensive to manufacture when special components are used to provide greater strength and stability. In addition, framework support structures of this type can present certain hazards to the user of the equipment. A snapped cable can emerge from the framework support structure and injure the user. Also, there is inadequate protection against inadvertent exposure of body parts, such as fingers, to certain of the internal working parts of the equipment and this too can lead to injury.

Only very light resistances can be used in this design or the framing and supports will bend and damage easily. It also requires the user to perform multiple steps to adjust the equipment for a desired exercise, particularly with regard to taking up the slack created in the cable when moving the egress point from place to place along the curved rod.

Other prior art that may be mentioned are the following U.S. Patent Nos.:

3,306,611	4,549,733	4,898,381	
5,018,725	5,102,122	5,195,937	5,725,459

However, none of these is all that relevant to the present invention.

Cable-cross units of equipment now currently available, provide a single step movable trolley that repositions an egress point along a straight bar, typically vertical in position, and typically have two such trolleys oriented side by side and spaced so a user can train in between them. Such designs do not optimize the interaction with basic human movement, do not provide a full 360-degree training environment in which to train, particularly limited in delivering resistance from training vectors overhead as well as

from below. Also, when switching from a linear track design to a curved track, cable slack and changes in length relative to the egress point and the cable end that connects to the attachment create a serious problem. To correct this problem, a counterweight system as shown in patent U.S. Patent No. 5,102,122 can be used. However, it calls for added steps to reposition the trolley due to the need to manually release the cable take-up means, unlock the trolley, move the trolley, relock the trolley and then relock the cable take-up means.

The current invention is related to the inventor's invention in U.S. Patent Application Serial No. 09/678,931, filed October 4, 2000, the contents of which are hereby incorporated herein by reference.

#### SUMMARY OF THE INVENTION

It is an object of this invention to provide a line of advanced pulley system exercise units of equipment which provide the user with the means to switch between a block and tackle set up (2:1 mechanical advantage system) and a direct lift set up in relation to the resistance means.

It is an object of this invention as well to allow the user to pull an attachment through a longer range and cut the incremental weight selection by half, thereby adding finer variations of resistance choices for the user to exercise with when using the 2:1 mechanical advantage system.

It is an object of this invention as well to provide the user with a 2:1 system that also reduces the inertial resistance during the execution of the outward pull, which gives a better feel to the movement and allows for higher speed training.

It is another object of this invention to provide a bilateral lifting system using multiple cables, the ends of which are directed by pulleys to positions where attachments can be connected at both ends of each cable. This allows users more choices of positions to choose from when training on a single machine, where resistance can be accomplished by inserting a single weight stack or other resistance means at the mid area of each cable.

These objects and others that will become apparent from the following specification may be achieved by exercise equipment including in one aspect a cable means attached at its distal end to a weight system, which cable means cooperates with pulley means for switching between a 2:1 mechanical advantage and a 1:1 ratio, the proximal end of the cable means being used to exert effort against the weight system. The weight system is variable. There may be a set of counterweights. The cable means that enables the user to exert force against the weight system may be a handle, strap, belt, rope, bar or leg curl.

Multiple cables may be used and when the equipment is set to operate as a 2:1 mechanical advantage system, the proximal end of a cable may be pulled around a pulley and simultaneously a counterweight at the distal end of the cable will rest against a stop, thereby creating an anchor at the distal end and completing the 2:1 mechanical advantage system.

An economy model of the exercise equipment includes a framed housing having a curved track defining a prescribed curved path, a pair of pulleys on a movable trolley repositionable along the curved path, and having passed between them a cable, the proximal end of which is located outside the curved track and attached to a means that enables the user to exert force against the resistance, to which the distal end of the cable

is attached. The resistance may be variable. The resistance may be a set of weights. A set of counterweights may be used to act as a cable-take-up means when different egress points along the curved track are utilized.

In another aspect of the exercise equipment, a bilateral lifting system comprises multiple cables, the ends of which are directed by pulleys to a position where their ends where attachments are connected at both ends of each cable with a single weight stack at the mid area of each cable. The cables pass through a set of multiple pulleys running parallel atop the weight stack and are directed by another series of pulleys to the respective egress points of the cables.

Means for allowing the user to exercise force against a resistance may be a handle, strap, belt, rope, bar or any other means that are useful in exercising.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front view of the 2:1 mechanical advantage system.

FIG. 2 is a top view of the 2:1 mechanical advantage system.

FIG. 3A is a side view of the adjustment module of the 2:1 mechanical advantage system.

FIG. 3B is a front view of part of the adjustment module of the 2:1 mechanical advantage system.

FIG. 3C is a side view of part of the adjustment module of the 2:1 mechanical advantage system.

FIG. 3D is a front view of the pulley part of the 2:1 mechanical advantage system.

FIG. 4 is a front view of the bilateral lifting system.

FIG. 5 is a top view of the bilateral lifting system.

## DETAILED DESCRIPTION OF THE INVENTION

FIGS. 1-3D illustrate a first aspect of the invention, i.e., the 2:1 mechanical advantage system.

FIGS. 4 and 5 illustrate a second aspect of the invention i.e., the bilateral lifting system.

It is advantageous to have a means whereby the user can easily switch between a block and tackle set up (2:1 mechanical advantage system) and a direct lift (1:1 ratio system) set up in relation to the resistance means. This adds the ability for the user to easily add stroke length to the egress end of the cable allowing the user to pull an attachment through a longer range and cuts the incremental weight selection by half, thereby adding finer variations of resistance choices for the user to exercise with when using the 2:1 mechanical advantage system. This 2:1 system also reduces the inertial resistance during the execution of the outward pull, which gives a better feel to the movement and allows for higher speed training.

FIG. 1 is a front view of the 2:1 mechanical advantage system.

FIG. 2 is a top view of the 2:1 mechanical advantage system.

FIG. 3A is a side view of the adjustment module of the 2:1 mechanical advantage system.

FIG. 3B is a front view of part of the adjustment module of the 2:1 mechanical advantage system.

FIG. 3C is a side view of part of the adjustment module of the 2:1 mechanical advantage system.

FIG. 3D is a front view of the pulley part of the 2:1 mechanical advantage system.

As far as possible, the reference numbering of the FIGS. follows that used in U.S. Patent Application Serial No. 09/678,931, filed October 4, 2000.

In FIG. 1, frame 41 of exercise equipment 40 provides means for other components of the equipment to be attached. The 2:1 mechanical advantage connector means is shown in FIGS. 1 and 3A as a rod-type pin could instead be a rod, bar, latch, switch or other type of connector means 1. Connector means 1 is inserted through a rod, bar, latch, switch or other type of cable linking means 2, which links cable 9.1 with cable 15.1 by two swaged balls 3 (or rod, bar, latch, switch or other type of other connector means) attached to the ends of cables 9.1 and 15.1, and then inserted into a rod, bar, latch, switch or other type of connector means 4. By inserting pin 1 through connector means 2 and connector means 4 which is attached to the pulley support 6 which is attached by the pulley bolt 11 inserted into lift stem 23 to make the connection with the resistance means 13, which is shown here as a weight stack.

When pin 1 is inserted through a rod, bar, latch, switch or other of type of connectors 2 and 4 and the user pulls on the attachment at the egress point of the cable, the weight stack is lifted with a 1:1 ratio of resistance. The cable slack created by cable 15.1 is taken up by a counter weight 16.1 connected at the distal end of cable 15.1 as it travels over redirectional pulleys 18.1 above, allowing it to drop into guide shaft 16.2.

When pin rod, bar, latch, switch or other type of connector 1 is removed, the lifting system turns into a 2:1 mechanical advantage block and tackle system. When an

exercise is performed, cable 15.1 is pulled around pulley 7 and, simultaneously, the counter weight 16.1 at the distal end of cable 15.1 nests against a stop block 16.3 and creates the anchor at this end to complete the 2:1 mechanical advantage system.

The cables 9 are horizontally redirected when they pass over pulleys 14.1 and then vertically downward as they pass over pulleys 14.2 where the distal ends of cables 9 are attached to counterweights 16. When the proximal end of a cable 9~~4~~ is pulled, it *RAF 9/26/01* raises the counterweights 16. A horizontal plate 18 with holes, slots or other openings cut so the cables 9 pass through the plate 18 is positioned above the counterweights 16 and extended over and attached or welded to a vertically positioned guiding means, e.g., a linear bearing 18.8 (or other guiding mechanism such as a roller system, or a bushing housed in a tube traveling on a rod, bar or other vertical support) traveling along a vertical shaft 20 positioned between the weight stack 13 and the counterweights 16. Single cable 9~~1~~ which is attached to the underside of horizontal plate 18 and to a pulley *RAF 9/26/01* 14.3 below, then routed upward to two pulleys 14.4 above the weight stack and down to a plate 13.1 to guide the weights 13 vertically along two upright guide rods 22 extending downward through the weight stack 13 and a rod 23 extending downward through the center of the weight stack with holes 24 cut in it to allow a selector pin 25 to slide into the weight stack 13 so the user can select the desired weight to lift. When the user pulls on the cable 9~~1~~ end at the point of egress, the counterweight 16 is lifted, thereby lifting the *RAF 9/26/01* horizontal plate assembly 18 and the selected weight 13. Other cables 9 in the system that are not engaged by the user at that time are held in the ready position by their respective counterweights 16.



The distal ends of the cables 9 are attached to a counterweight 16, which travels vertically through a slot mounted in a housing with each slot and counterweight 16 positioned side by side at the end of each respective cable 9, (one counterweight 16 for each cable 9 threaded through the system) positioned next to the resistance, which in this case is a set of weights 13, and housed within a vertical set of guide tracks 17. They are positioned within the housing on the far side of the weights, but could be positioned in other arrangements relative to the resistance. Optimal positioning is next to or adjacent to the resistance. The counterweights 16 are optimally also positioned at or slightly beneath the top plane of the weight stack 16, but could be positioned above the top plate.

FIG. 4 is a front view of the bilateral lifting system.

FIG. 5 is a top view of the bilateral lifting system.

Frame 61 of a bilateral lifting system 60 uses multiple cables 62 and 63, having two ends directed by pulleys 64 to where attachments can be connected at both ends of each cable 62 and 63. Using both ends of cables 62 and 63 allows users more choices of positions to choose from when training on a single machine and can be accomplished by inserting a single weight stack 65 or other resistance means at the mid area of each cable 62 and 63. The cables 62 and 63 may pass through a set of multiple pulleys 66 running parallel atop the weight stack 65 and directed by a series of pulleys 64 to the respective egress points of cables 62 and 63. Such a system can be used in connection with the first aspect of the current invention and can also be used in connection with other exercise equipment currently on the market such as the CYBEX FT 360 or the similar unit by Ground Zero.

The foregoing specification and drawings have thus described and illustrated novel improvements in exercise systems that fulfill all of the objects and advantages sought therefor. Many changes, modifications, variations and other uses and applications of the subject invention will, however, become apparent to those skilled in the art after considering this specification which discloses the preferred embodiments thereof. All such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention, which is to be limited only by the claims which follow.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000